

LCD Panel	Diagonal Size	100-inch
	LCD Panel	Commercial A+ Grade LCD Panel
	Resolution	3840 x 2160 @ 60Hz
	Pixel Pitch	0.19125(H) x 0.5735(V)
	Display Active Area	2199.7 mm x 1307.7mm
	Brightness	350 cd/m ² (typical)
	Dynamic Contrast Ratio	4000:1
	Display Colors	16.7 bit
	View Angle	178° (H) /178° (V)
	Response Time	≤ 8ms
	Working Hour	7x 24 hours
	Panel Life	≥50000 hours
	Tempered Glass	4mm Tempered protection glass
	Built-in Mainboard	HDMI
USB		1 x USB input
Built-in Louder Speaker		2 x 8Ω 5W louder speaker
Other	Power Consumption	≤150W (Typ)
	Power Supply Voltage	AC240V to 110V (50 HZ/ 60HZ)
	Outline Dimension	2270.2mm(W) x 1306.7mm(H) x 112.8mm(D)
	Mechanical Enclosure	Industrial Metal steel enclosure with black color
	Working Temperature	0 °C ~ 40 °C
	Working Humidity	10 %-90% (No-Condensing)
	Storage Temperature	0 °C ~ 40 °C
	Storage Humidity	10% ~90%(No Condensing)

Outline Dimension(mm)

